



CASTROL AIRCOL 229 RANGE

Synthetic Refrigeration Compressor Lubricant

Description

The Aircol 229 range of refrigeration oils are formulated from selected polyalphaolefin base stocks.

Application

They are specifically designed for use in refrigeration systems using screw type compressors combined with very low evaporator temperatures. They may also be specified for certain systems using reciprocating compressors with high compression ratios and discharge temperatures.

The very low pour points enable the Aircol 229 range to be used in systems where evaporator temperatures are extremely low.

However because of their low miscibility with R22 the Aircol 229 range oils are not suitable for use in refrigeration systems using flooded evaporators, unless efficient oil separators or some other method of oil recovery is provided.

Features / Benefits

The Aircol 229 range is designed to have low miscibility and solubility with R22. This characteristic gives significant advantages in screw type compressors where refrigerant absorption can adversely affect volumetric efficiency and reduce lubricant viscosity to unacceptably low levels.

Technical Data

Name	Method	Units	Aircol 2294	Aircol 2295
Density @ 15°C	ASTM D4052	g/ml	0.84	0.85
Viscosity @ 40°C	ASTM D445	mm ² /s	68	220
Viscosity @ 100°C	ASTM D445	mm ² /s	10.8	25.2
Closed Flash Point	ASTM D93	°C	233	243
Pour Point	ASTM D97	°C	-45	-40

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60C, exposed to hot sun or freezing conditions.

CASTROL AIRCOL 229 RANGE

19 Apr 2011

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrolmarine.com