

Aircol SN 100

Synthetic Air Compressor Lubricant

Description

Castrol Aircol™ SN 100 compressor lubricant is high quality synthetic diester.

Application

Castrol Aircol SN 100 is a compressor lubricant developed to cope with the severe operating conditions experienced in rotary screw, rotary vane and reciprocating air compressors operating at high compression ratios and high discharge temperatures. Under these conditions Aircol SN 100 offers much reduced carbon forming tendencies and extended oil life when compared to mineral oils due to the much higher oxidation resistance. In reciprocating units, Aircol SN 100 has up to eight times the service life of mineral oils.

Advantages

- Superior oxidation stability.
- Improved lubricity and film strength.
- Higher film strength and excellent anti-wear properties.
- Excellent high temperature performance.
- Reduced maintenance, extended oil life and cleaner operations, minimises carbon formulation and provides extended valve life.
- Reduced oil consumption due to a reduction in the feed rate to the cylinder walls and piston rings without increasing wear rates. Since less lubricant is consumed the downstream air is also of higher quality.
- Reduced compressor down-time due to less wear on all moving parts, longer machine life and reduced maintenance.
- The operating range of Aircol SN 100 extends well beyond that of conventional mineral oils. The high spontaneous ignition temperature gives greater safety by reducing the possibility of downstream fires and explosions.

Typical Characteristics

Name	Method	Units	Aircol SN 100
ISO Viscosity Grade	-	-	100
Relative Density at 15°C	ISO 12185, ASTM D4052	g/ml	0.96
Kinematic Viscosity at 40°C	ISO 3104, ASTM D445	mm ² /s	100
Kinematic Viscosity at 100°C	ISO 3104, ASTM D445	mm ² /s	10.3
Viscosity Index	ISO 2909, ASTM D2270	-	89
Flash Point, COC	ISO 2592, ASTM D92	°C	>200
Pour Point	ISO 3016, ASTM D97	°C	-40

Subject to usual manufacturing tolerances.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing condition

Aircol SN 100

12 Apr 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193 , South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za