



## AIRCOL 228 Range

Synthetic Refrigeration Compressor Lubricant

### Description

The Aircol 228 range of refrigeration oils is formulated from selected alkyl-benzene base stocks.

### Application

Suitable for use in R22 refrigeration systems with very low evaporator temperatures where Alkyl-benzene based lubricants are recommended by the manufacturer. These products may not be suitable for use in refrigeration systems employing screw compressors due to the high level of solubility of refrigerant in the lubricant, which may reduce its viscosity to unacceptable levels. However this is largely dependent on operating conditions.

Castrol Aircol 2284 can also be used in ammonia refrigeration compressors where an ISO VG 68 Alkyl-benzene based lubricant is recommended.

### Features / Benefits

- The Castrol Aircol 228 range of refrigeration oils has excellent miscibility and solubility characteristics with R22.
- The very low floc points enable the Aircol 228 range to be used in systems where evaporator temperatures are extremely low.

### Technical Data

Name	Method	Units	Aircol 2284	Aircol 2285
Density @ 15°C	ASTM D4052	g/ml	0.86	0.87
Kinematic Viscosity 40°C	ASTM D445	cSt	68	100
Closed Flash Point	ASTM D93	°C	165	175
Pour Point	ASTM D97	°C	-33	-30
Floc Point, R22	DIN 51351	°C	-55	-50

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

### Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

## Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60C, exposed to hot sun or freezing conditions.

AIRCOL 228 Range

13 Apr 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

[www.castrolmarine.com](http://www.castrolmarine.com)