



Castrol EDGE Professional V 0W-20

Strength to Perform - Freedom to Drive

Description

Castrol EDGE Professional with *Fluid Strength Technology™* is Castrol's strongest and most advanced range of engine oils.

Its unique adaptive strength reduces metal to metal contact across a range of different driving speeds.

Castrol EDGE Professional - lowers friction and maximises engine performance.

Castrol EDGE Professional V 0W-20 gives you the confidence to demand maximum engine performance from today's modern, higher revving sports cars and luxury vehicles requiring lower viscosity oils.

Castrol EDGE Professional V 0W-20 is co-engineered in partnership with Volvo cars for the latest generation engines. Micro-filtered and with its signature fluorescent colour it is your guarantee of Professional quality.

Castrol EDGE Professional. Strength to Perform - Freedom to Drive.

Application

Castrol EDGE Professional V 0W-20 is suitable for use in automotive gasoline engines where the manufacturer recommends an oil approved to Volvo VCC RBS0-2AE and SAE 0W-20 grade.

Castrol EDGE Professional V 0W-20 is exclusively approved for Volvo cars that require Volvo VCC RBS0-2AE.

Advantages

Castrol EDGE Professional V 0W-20:

- Maximises short and long term engine performance
- Sustains maximum performance for longer, even when under pressure
- Improves engine efficiency, independently qualified
- Delivers unsurpassed levels of protection across a variety of driving speeds

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional V 0W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.8421
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.8
Viscosity, CCS -35C	ASTM D5293	mPa.s (cP)	4600
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	47
Viscosity Index	ASTM D2270	None	171
Ash, Sulphated	ASTM D874	% wt	0.83
Pour Point	ASTM D97	°C	-54
Flash Point, PMCC	ASTM D93	°C	206

Product Performance Claims

VCC RBS0-2AE

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional V 0W-20

21 Nov 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za