



## Technical Data Sheet

### CASTROL MOTOR OIL 40

#### DESCRIPTION:

Castrol Motor Oil 40 is premium grade monograde engine oil, which complies with the API SF Classification.

#### APPLICATION:

This grade is recommended for use in petrol engines fitted to passenger cars and commercial vehicles where SAE 40 monograde oil is specified.

#### BENEFITS:

- Satisfies engine manufacturers' warranties as a monograde where API SF is specified.
- Good control of sludge and deposits under adverse operating conditions.
- Excellent anti-wear and anti-corrosion additives.

#### SPECIFICATIONS:

API SF  
SAE 40

TYPICAL CHARACTERISTICS	Castrol Motor Oil
Product Code	33590
Density at 15°C	0.892
Viscosity at 40°C mm <sup>2</sup> /s	144
Viscosity at 100°C mm <sup>2</sup> /s	14.3
Viscosity Index	95
Flash Point °C (COC)	218.3
Pour Point °C	-12
Total Base Number - TBN	5.26
Sulphate Ash %	0.6
SAE Rating	40

Last Edited: 31 October 2016

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence. The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory right of the Buyer of the petroleum product concerned)