



## Castrol Motor Oil 25W-50

Basic engine wear protection

### Description

Castrol Motor Oil 25W-50 offers protection for older generation normally aspirated and turbocharged petrol and diesel engines.

### Application

Castrol Motor Oil 25W-50 is suitable for use in automotive petrol and diesel engines where the manufacturer recommends and API SG/CF or earlier specification lubricant.

### Advantages

Castrol Motor Oil 25W-50 offers the following benefits:

- Good start up and high temperature engine wear protection.
- Assists with reducing oil consumption.
- High level of fuel dilution capability.
- Excellent viscosity stability
- Good oil pressure control

### Typical Characteristics

Name	Method	Units	Castrol Motor Oil 25W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.897
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	18.59
Viscosity, CCS -10C (25W)	ASTM D5293	mPa.s (cP)	11631
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	199.7
Viscosity Index	ASTM D2270	None	103
Pour Point	ASTM D97	°C	-30
Flash Point, PMCC	ASTM D93	°C	210
Ash, Sulphated	ASTM D874	% wt	0.68

# Product Performance Claims

API SG/CF

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Motor Oil 25W-50

22 Aug 2013

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

10 Junction Avenue , Parktown , Johannesburg , 2193, South Africa  
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)  
[www.castrol.co.za](http://www.castrol.co.za)